TerraCair Ultrapure Diesel Exhaust Fluid 330 Gallon IBC- Closed System

The recommended solution to maintain product integrity

DEF Information

DEF is designed for use in diesel engines with SCR technology. This package will provide for approximately 99,000 miles (your results may vary depending on your vehicle and dosage rate.)

Chemical Data

- Diesel Exhaust Fluid
- Meets AUS 32, ISO 22241 and DIN 70070 Specification
- Weight- 9.1 lbs. per gallon (1.09 kg per liter)
- Non Hazardous
- 32.5 % automotive grade urea/D1 water
- Clear
- Crystallizes at 12°F (-11°C)
- Ideal Storage 23°F to 86°F (-5°C to 30°C)

Package Data

- Holds 330 US Gallons/1,250 Liters
- Dimensions (LxWxH) 47.24" x 39.37" x 53.15"
- 3,300 lbs net weight
- Delivered by truck, off loaded by customer fork lift
- NAFTA compliant label in English, French, and Spanish

IBC Return Policy

- Returnable to Hawkins, Inc., requires a deposit
- Can be refilled on-site

Sealed System

- Pump required for dispensing
- Sealed connection system ensures no contamination
- Stainless Micro Matic "female" quick connection system

Equipment Options (sold separately)

- Hand pump with 19mm nozzle rated for DEF
- Electric pump with 19mm nozzle rated for DEF









